DATA SHEET

Latest update
1-07-2026

AGRIMAX SPARGO



TIRE SIZE	**VF 480/95 R 50**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	181 D

DIMENSIONS IS STANDARD

SW (MM)	479	**RIM REC**	DW 16 L
OD (MM)	2182	**RIM ALT**	DW 15 L
SLR (MM)	991	**ECE**	E11-106R-0010083
RC (MM)	6606	**SRI**	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	4045	4500	5035	5495	5800	6025	6255	6485	6790	7095	7325	7630
FROM 65 TO 40	4375	4865	5445	5940	6270	6515	6765	7015	7345	7675	7920	8250
30	4460	4960	5550	6060	6400	6645	6900	7155	7490	7825	8080	8415
20	4550	5060	5660	6180	6525	6775	7035	7295	7635	7980	8240	8580
10	4810	5350	5985	6535	6900	7165	7440	7715	8075	8440	8715	9075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..