

# AGRIMAXFACTOR

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 620/70 R 46                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR                                                                                  |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 162 D ; 165 A8                                                                           |



## DIMENSIONS IS STANDARD

|          |      |          |                  |
|----------|------|----------|------------------|
| SW (MM)  | 625  | RIM REC  | DW 20 B          |
| OD (MM)  | 2036 | ECE      | E11-106R-0010339 |
| SLR (MM) | 913  | SRI      | 975              |
| RC (MM)  | 6075 | TRA CODE | R1W              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 2615 | 3040 | 3470 | 3895 | 4325 | 4750 |
| 50         | 2745 | 3195 | 3645 | 4095 | 4545 | 4990 |
| 40         | 2865 | 3335 | 3800 | 4270 | 4740 | 5205 |
| 30         | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |
| 10 LT      | 3505 | 4075 | 4650 | 5220 | 5795 | 6365 |
| 10HT       | 3010 | 3500 | 3990 | 4485 | 4975 | 5465 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.