DATA SHEET

Latest update
4-07-2026

FL 630 SUPER



TYRE SIZE	**710/50 R 30.5**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	173 D

DIMENSIONS IS STANDARD

SW (MM)	686	**RIM REC**	AG 20.00
OD (MM)	1485	**RIM ALT**	AG 24.00
SLR (MM)	676	**ECE**	E11-106R-0010340
RC (MM)	4550	**SRI**	700

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1835	2130	2430	3020	3435	4025	4500	4910	5385	5915
65	2015	2340	2665	3315	3770	4420	4940	5395	5915	6500
50	2440	2835	3225	4015	4565	5350	5980	6530	7160	7865
40	2745	3185	3625	4510	5130	6015	6720	7340	8045	8840
25	3185	3700	4215	5240	5960	6985	7810	8525	9350	10270
10	3630	4215	4800	5970	6790	7960	8895	9715	10650	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..