DATA SHEET

Latest update
4-08-2026

V-FLEXA



TYRE SIZE	**VF 800/45 R 26.5**
UM	IS STANDARD
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	179 D

DIMENSIONS IS STANDARD

SW (MM)	805	**RIM ALT**	AG 24.00
OD (MM)	1393	**ECE**	E11-106R-0010576
SLR (MM)	602	**SRI**	675
RC (MM)	4213	**TREAD DEPTH (MM)**	26,5
RIM REC	AG 28.00		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2	2.4	2.8	3.2
70	2825	3600	4235	4940	5575	6350	7055
65	3100	3955	4650	5425	6125	6975	7750
50	3630	4630	5445	6350	7170	8165	9070
40	4000	5100	6000	7000	7900	9000	10000
10	5085	6485	7630	8900	10045	11440	12710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.