

AGRIMAX RT 600

TYRE SIZE	IF 710/75 R 34 CFO
UM	IS STANDARD
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	184 A8/B



DIMENSIONS IS STANDARD

SW (MM)	715	RIM ALT	DW23 B
OD (MM)	1920	ECE	E11-106R-0010577
SLR (MM)	856	SRI	900
RC (MM)	5771	TREAD DEPTH (MM)	56
RIM REC	DW25 B		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	3510	4140	4770	5310	5940	6480	7110	7650	8370	9000
40	3510	4140	4770	5310	5940	6480	7110	7650	8370	9000
30	3655	4310	4965	5525	6180	6740	7395	7960	8705	9360
10	4460	5260	6060	6745	7545	8230	9030	9720	10630	11430
UPTO 30 CYC	4565	5385	6205	6905	7725	8425	9245	9945	10885	11700
UPTO 15 CYC	5445	6420	7395	8235	9210	10045	11025	11860	12975	13950
UPTO 10 CYC	5970	7040	8110	9030	10100	11020	12090	13005	14230	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.