

# AGRIMAX V-FLECTO



|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>VF 480/70 R 34 NRO</b>                                                                |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 166 D                                                                                    |

## DIMENSIONS IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 495  | <b>RIM REC</b> | W 18 L           |
| <b>OD (MM)</b>  | 1580 | <b>RIM ALT</b> | W 16 L ; DW 18 L |
| <b>SLR (MM)</b> | 708  | <b>ECE</b>     | E11-106R-0010578 |
| <b>RC (MM)</b>  | 4739 | <b>SRI</b>     | 750              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  | 2    | 2.4  | 2.8  | 3.2  |
|--------------------------------|------|------|------|------|------|------|------|------|------|------|
| 70                             | 1880 | 2220 | 2555 | 2845 | 3185 | 3475 | 3810 | 4100 | 4485 | 4820 |
| FROM 65 TO 40                  | 2070 | 2440 | 2810 | 3130 | 3500 | 3820 | 4190 | 4505 | 4930 | 5300 |
| 30                             | 2110 | 2490 | 2865 | 3190 | 3570 | 3895 | 4270 | 4595 | 5030 | 5405 |
| 20                             | 2150 | 2535 | 2925 | 3255 | 3640 | 3970 | 4355 | 4685 | 5125 | 5510 |
| 10                             | 2275 | 2685 | 3090 | 3440 | 3850 | 4200 | 4610 | 4960 | 5425 | 5830 |
| *UPTO 10 CYC WITH FRONT LOADER | 2895 | 3415 | 3935 | 4380 | 4900 | 5345 | 5865 | 6310 | 6905 | 7420 |
| 10HT                           | 2110 | 2490 | 2865 | 3190 | 3570 | 3895 | 4270 | 4595 | 5030 | 5405 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.