

AGRIMAX V-FLECTO

TIRE SIZE	VF 480/80 R 50 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STEEL BELTED SPL
TL/TT	TL
LI/SS	179 D



DIMENSIONS IS STANDARD

SW (MM)	479	RIM REC	DW16L
OD (MM)	2038	RIM ALT	DW15L
SLR (MM)	938	ECE	E11-106R-0010595
RC (MM)	6195	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
70	2610	3035	3455	3950	4375	4795	5290	5570	6135	6630	7050
FROM 65 TO 40	2870	3335	3800	4340	4805	5270	5815	6125	6745	7285	7750
30	2925	3400	3875	4430	4905	5380	5930	6245	6880	7435	7905
20	2985	3470	3950	4515	5000	5485	6045	6370	7015	7580	8060
10	3155	3670	4180	4775	5290	5800	6395	6735	7420	8015	8525
UPTO 30 CYCLIC	3255	3785	4310	4930	5455	5985	6600	6950	7655	8270	8795
UPTO 15 CYCLIC	3885	4515	5145	5880	6510	7140	7875	8295	9135	9870	10500
UPTO 10 CYCLIC	4260	4950	5640	6445	7135	7825	8630	9090	10010	10815	11505
10HT	2925	3400	3875	4430	4905	5380	5930	6245	6880	7435	7905

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.