DATA SHEET

Latest update
4-08-2026

V-FLEXA



TYRE SIZE	**VF 800/60 R 32**
UM	IS STANDARD
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	191 D

DIMENSIONS IS STANDARD

SW (MM)	818	**RIM ALT**	DW 25 B
OD (MM)	1799	**ECE**	E11-106R-0010632
SLR (MM)	785	**SRI**	850
RC (MM)	5459	**TREAD DEPTH (MM)**	27,5
RIM REC	DW 27 B		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2
70	3970	5060	5955	6945	7840	8930	9920
65	4360	5560	6540	7630	8615	9810	10900
50	5105	6510	7655	8930	10080	11480	12755
40	5630	7175	8440	9850	11115	12660	14065
10	7155	9120	10730	12520	14130	16095	17880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.