

AGRIMAX PROHARVEST

TIRE SIZE	VF 800/70 R 32 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HARVESTER
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	187 D



DIMENSIONS IS STANDARD

SW (MM)	804	RIM REC	DW 28 B
OD (MM)	1933	RIM ALT	DW 27 B; DW 30 B
SLR (MM)	846	ECE	E11-106R-0010664
RC (MM)	5817	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4165	4785	5495	6205	6915	7625	8335	8870
FROM 65 TO 40	4580	5265	6045	6825	7605	8385	9165	9750
30	4670	5370	6165	6960	7755	8550	9345	9945
20	4765	5475	6285	7095	7905	8720	9530	10140
10	5040	5790	6645	7505	8365	9220	10080	10725
UPTO 30 CYC	5200	5975	6860	7745	8630	9515	10400	11065
UPTO 15 CYC	6205	7130	8190	9245	10300	11360	12415	13210
UPTO 10 CYC	6800	7815	8970	10130	11290	12445	13605	14475
10HT	4670	5370	6165	6960	7755	8550	9345	9945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.