

MULTIMAX MP 522

TIRE SIZE	540/70 R 24 IND
UM	IS STANDARD
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	168 A8/B



DIMENSIONS IS STANDARD

OD (MM)	1366	RIM ALT	DW 18 L
SLR (MM)	611	ECE	E11-106R-002967
RC (MM)	4133	SRI	650
RIM REC	DW 16 L	TREAD DEPTH (MM)	42,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2690	3195	3640	4145	4650	4985	5600	-	-
40	2690	3195	3640	4145	4650	4985	5600	-	-
30	2880	3420	3900	4440	4980	5340	5995	-	-
25	2990	3550	4045	4605	5165	5540	6220	-	-
10 CYC.	3280	4035	4750	5460	6220	6765	7645	8065	8400
STATIC	5025	6185	7280	8375	9535	10370	11725	12365	12880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.