

RIDEMAX FL 693 M



TIRE SIZE	650/55 R 26.5
UM	IS STANDARD
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	HD
TL/TT	TL
LI/SS	178 D

DIMENSIONS IS STANDARD

SW (MM)	645	RIM REC	AG 20.00
OD (MM)	1389	ECE	E11-106R-003008
SLR (MM)	615	SRI	650
RC (MM)	4250	TREAD DEPTH (MM)	23,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	2325	2775	3375	3900	4500	5100	5475	6075	6675	7050	7500
50	2815	3360	4085	4720	5445	6175	6625	7355	8080	8535	9075
40	3165	3775	4590	5305	6120	6940	7450	8265	9080	9590	10200
30	3515	4195	5100	5890	6795	7705	8270	9175	10080	10650	11325
25	3675	4385	5335	6165	7110	8060	8655	9600	10550	11140	11850
10	4185	4995	6075	7020	8100	9180	9855	10935	12015	12690	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.