

# CON STAR

|                  |                                                                |
|------------------|----------------------------------------------------------------|
| <b>TYRE SIZE</b> | <b>400/70 - 20</b>                                             |
| <b>UM</b>        | IS STANDARD                                                    |
| <b>MACHINERY</b> | COMPACT LOADER / TELEHANDLER /<br>COMPACT LOADER / TELEHANDLER |
| <b>VERSION</b>   | INDUSTRIAL                                                     |
| <b>TL/TT</b>     | TL                                                             |
| <b>LI/SS</b>     | 149 A8                                                         |



## DIMENSIONS IS STANDARD

|                 |      |                |                      |
|-----------------|------|----------------|----------------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | 13                   |
| <b>OD (MM)</b>  | 1080 | <b>RIM ALT</b> | 12 SDC ; 13 SDC ; 14 |
| <b>SLR (MM)</b> | 501  | <b>ECE</b>     | E11-106R-003024      |
| <b>RC (MM)</b>  | 3303 | <b>PR</b>      | 16                   |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 40                | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.