

## LG 306

|                  |                                 |
|------------------|---------------------------------|
| <b>TIRE SIZE</b> | <b>18X9.50 -8</b>               |
| <b>UM</b>        | IS STANDARD                     |
| <b>MACHINERY</b> | MOWER / SMALL TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                        |
| <b>TL/TT</b>     | TL                              |



### DIMENSIONS IS STANDARD

|                 |      |                         |                               |
|-----------------|------|-------------------------|-------------------------------|
| <b>SW (MM)</b>  | 230  | <b>RIM REC</b>          | 7.00 I - 55 ; I - 70 ; I - 90 |
| <b>OD (MM)</b>  | 470  | <b>ECE</b>              | E11-106R-003449               |
| <b>SLR (MM)</b> | 206  | <b>PR</b>               | 4                             |
| <b>RC (MM)</b>  | 1363 | <b>TREAD DEPTH (MM)</b> | 7,7                           |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.40</b> |
| 15                | 425         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.