

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TYRE SIZE</b> | <b>420/85 R 26</b> |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TL/TT</b>     | TL                 |
| <b>LI/SS</b>     | 138 A8/B           |



### DIMENSIONS IS STANDARD

|                 |         |                         |                                    |
|-----------------|---------|-------------------------|------------------------------------|
| <b>SW (MM)</b>  | 450     | <b>RIM ALT</b>          | W 14 L ; W 15 L ; W 16 L ; DW 16 L |
| <b>OD (MM)</b>  | 1374    | <b>ECE</b>              | E11-106R-003471                    |
| <b>SLR (MM)</b> | 616     | <b>SRI</b>              | 650                                |
| <b>RC (MM)</b>  | 4115    | <b>TRA CODE</b>         | R1                                 |
| <b>RIM REC</b>  | DW 15 L | <b>TREAD DEPTH (MM)</b> | 40,5                               |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 1300 | 1515 | 1725 | 1940 | 2150 | 2360 |
| <b>40</b>    | 1300 | 1515 | 1725 | 1940 | 2150 | 2360 |
| <b>30</b>    | 1395 | 1620 | 1850 | 2075 | 2305 | 2530 |
| <b>10 LT</b> | 1745 | 2030 | 2315 | 2600 | 2885 | 3165 |
| <b>10 HT</b> | 1395 | 1620 | 1850 | 2075 | 2305 | 2530 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.