

# TRAC MASTER

|                  |                                               |
|------------------|-----------------------------------------------|
| <b>TYRE SIZE</b> | <b>300/60 - 12</b>                            |
| <b>UM</b>        | IS STANDARD                                   |
| <b>MACHINERY</b> | IMPLEMENT MACHINERY / TRACTOR /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                      |
| <b>TL/TT</b>     | TL                                            |



## DIMENSIONS IS STANDARD

|                 |      |                         |                 |
|-----------------|------|-------------------------|-----------------|
| <b>SW (MM)</b>  | 306  | <b>RIM ALT</b>          | 9.5             |
| <b>OD (MM)</b>  | 645  | <b>ECE</b>              | E11-106R-003597 |
| <b>SLR (MM)</b> | 285  | <b>PR</b>               | 8               |
| <b>RC (MM)</b>  | 1885 | <b>TREAD DEPTH (MM)</b> | 18              |
| <b>RIM REC</b>  | 10.5 |                         |                 |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.20</b> |
| 50                | 1030        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.