

## AGRIMAX RT 600

|                  |                      |
|------------------|----------------------|
| <b>TYRE SIZE</b> | <b>650/75 R 32</b>   |
| <b>UM</b>        | IS STANDARD          |
| <b>MACHINERY</b> | TRACTOR / IMPLEMENTS |
| <b>VERSION</b>   | STANDARD             |
| <b>TL/TT</b>     | TL                   |
| <b>LI/SS</b>     | 172 A8/B             |



### DIMENSIONS IS STANDARD

|                 |         |                         |                   |
|-----------------|---------|-------------------------|-------------------|
| <b>SW (MM)</b>  | 655     | <b>RIM ALT</b>          | DW 20 B ; DW 23 B |
| <b>OD (MM)</b>  | 1789    | <b>ECE</b>              | E11-106R-004755   |
| <b>SLR (MM)</b> | 807     | <b>SRI</b>              | 850               |
| <b>RC (MM)</b>  | 5416    | <b>TREAD DEPTH (MM)</b> | 49,5              |
| <b>RIM REC</b>  | DW 21 B |                         |                   |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR     | 0.8  | 1.0  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2   | 3.4   | 3.8   |
|----------------|------|------|------|------|------|------|------|-------|-------|-------|
| <b>50</b>      | 2900 | 3340 | 4095 | 4475 | 4915 | 5355 | 5800 | 6300  | -     | -     |
| <b>40</b>      | 2900 | 3340 | 4095 | 4475 | 4915 | 5355 | 5800 | 6300  | -     | -     |
| <b>30</b>      | 3105 | 3575 | 4385 | 4790 | 5265 | 5735 | 6210 | 6745  | -     | -     |
| <b>10 LT</b>   | 3885 | 4480 | 5490 | 6000 | 6590 | 7180 | 7770 | 8445  | -     | -     |
| <b>10 HT</b>   | 3105 | 3575 | 4385 | 4790 | 5265 | 5735 | 6210 | 6745  | -     | -     |
| <b>10 CYC.</b> | -    | 4770 | 6105 | 6695 | 7765 | 8515 | 9320 | 10125 | 10285 | 10710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.