

## FL 630 SUPER

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 600/55 R 22.5                                                                            |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRAILER / IMPLEMENTS                                                                     |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 162 D                                                                                    |



### DIMENSIONS IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 595  | RIM REC | AG 20.00        |
| OD (MM)  | 1232 | ECE     | E11-106R-004759 |
| SLR (MM) | 560  | SRI     | 575             |
| RC (MM)  | 3757 |         |                 |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|
| 70         | 1580 | 1775 | 2210 | 2510 | 2900 | 3290 | 3590 | 3940 | 4325 |
| 65         | 1735 | 1950 | 2425 | 2755 | 3185 | 3610 | 3945 | 4325 | 4750 |
| 50         | 2100 | 2360 | 2935 | 3335 | 3855 | 4370 | 4775 | 5235 | 5750 |
| 40         | 2360 | 2650 | 3295 | 3750 | 4330 | 4910 | 5365 | 5880 | 6460 |
| 25         | 2740 | 3080 | 3830 | 4355 | 5030 | 5705 | 6230 | 6830 | 7505 |
| 10         | 3125 | 3510 | 4365 | 4960 | 5730 | 6500 | 7100 | 7785 | 8550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.