

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | IF 420/85 R 38                                                                           |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 155 D                                                                                    |



## DIMENSIONS IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 419  | RIM REC | DW 14 L         |
| OD (MM)  | 1670 | RIM ALT | DW 15 L         |
| SLR (MM) | 780  | ECE     | E11-106R-004897 |
| RC (MM)  | 5017 | SRI     | 800             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------------------------|------|------|------|------|------|------|------|------|
| 70                             | 1655 | 1900 | 2180 | 2465 | 2745 | 3030 | 3310 | 3525 |
| FROM 65 TO 40                  | 1820 | 2090 | 2400 | 2710 | 3020 | 3330 | 3640 | 3875 |
| 30                             | 1890 | 2170 | 2495 | 2815 | 3140 | 3460 | 3785 | 4030 |
| 20                             | 1965 | 2255 | 2590 | 2925 | 3260 | 3595 | 3930 | 4185 |
| 10                             | 2310 | 2650 | 3045 | 3440 | 3835 | 4225 | 4620 | 4920 |
| *UPTO 10 CYC WITH FRONT LOADER | 2545 | 2925 | 3360 | 3790 | 4225 | 4660 | 5095 | 5425 |
| 10 HT                          | 1890 | 2170 | 2495 | 2815 | 3140 | 3460 | 3785 | 4030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.