DATA SHEET

Latest update
3-08-2026

RIDEMAX IT 697 (M+S)



TIRE SIZE	**600/65 R 38 IND**
UM	IS STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	166 D ; 170 A8

DIMENSIONS IS STANDARD

SW (MM)	590	**RIM ALT**	DW 20 B
OD (MM)	1745	**ECE**	E11-106R-005855
SLR (MM)	795	**SRI**	825
RC (MM)	5315	**TREAD DEPTH (MM)**	30,5
RIM REC	DW 18 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	2490	3075	3605	4185	4715	5300
50	2690	3320	3895	4525	5095	5725
40	2820	3480	4080	4740	5340	6000
30	2990	3690	4325	5025	5660	6360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.