

# AGRIMAX RT 765

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 650/75 R 38                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR / IMPLEMENTS                                                                     |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 169 D                                                                                    |



## DIMENSIONS IS STANDARD

|          |      |         |                   |
|----------|------|---------|-------------------|
| SW (MM)  | 655  | RIM REC | DW 21 B           |
| OD (MM)  | 1941 | RIM ALT | DW 20 B ; DW 23 B |
| SLR (MM) | 874  | ECE     | E11-106R-006161   |
| RC (MM)  | 5820 | SRI     | 925               |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2730 | 3135 | 3600 | 4060 | 4525 | 4990 | 5455 | 5800 |
| 50         | 2865 | 3290 | 3780 | 4265 | 4755 | 5240 | 5725 | 6090 |
| 40         | 2990 | 3435 | 3945 | 4450 | 4960 | 5470 | 5975 | 6355 |
| 30         | 3135 | 3605 | 4140 | 4670 | 5205 | 5740 | 6270 | 6670 |
| 10 LT      | 3655 | 4200 | 4825 | 5445 | 6065 | 6690 | 7310 | 7775 |
| 10 HT      | 3135 | 3605 | 4140 | 4670 | 5205 | 5740 | 6270 | 6670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.