

AGRIMAX V-FLECTO

TIRE SIZE	VF 650/60 R 38 NRO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	173 D



DIMENSIONS IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1745	RIM ALT	DW 21 B
SLR (MM)	774	ECE	E11-106R-006415
RC (MM)	5217	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2725	3135	3610	4025	4500	4910	5505	5915
FROM 65 TO 40	2990	3445	3965	4420	4940	5395	6045	6500
30	3050	3515	4045	4510	5040	5504	6170	6630
20	3110	3585	4125	4600	5140	5615	6290	6760
10	3290	3790	4365	4865	5435	5935	6650	7150
*UPTO 10 CYC WITH FRONT LOADER	4190	4825	5555	6190	6920	7555	8465	9100
10 HT	3050	3515	4045	4510	5040	5505	6170	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.