

# MULTIMAX MP 513

|                  |                                                             |
|------------------|-------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>425/55 R 17 MPT</b>                                      |
| <b>UM</b>        | IS STANDARD                                                 |
| <b>MACHINERY</b> | UNIVERSAL VEHICLE / FERTILIZER<br>TRUCK / UNIVERSAL VEHICLE |
| <b>VERSION</b>   | STANDARD                                                    |
| <b>TL/TT</b>     | TL                                                          |
| <b>LI/SS</b>     | 142 A8/B                                                    |



## DIMENSIONS IS STANDARD

|                 |      |                         |                 |
|-----------------|------|-------------------------|-----------------|
| <b>OD (MM)</b>  | 900  | <b>RIM ALT</b>          | 13.00           |
| <b>SLR (MM)</b> | 399  | <b>ECE</b>              | E11-106R-006433 |
| <b>RC (MM)</b>  | 2705 | <b>TREAD DEPTH (MM)</b> | 27,5            |
| <b>RIM REC</b>  | 13   |                         |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  |
|------------|------|------|------|------|------|------|------|------|
| 50         | 1035 | 1275 | 1515 | 1725 | 1965 | 2200 | 2440 | 2650 |
| 40         | 1035 | 1275 | 1515 | 1725 | 1965 | 2200 | 2440 | 2650 |
| 30         | 1110 | 1365 | 1620 | 1850 | 2105 | 2360 | 2530 | 2840 |
| 25         | 1150 | 1415 | 1680 | 1915 | 2180 | 2445 | 2625 | 2945 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.