

AGRIMAX V- FLECTO



TIRE SIZE	VF 580/85 R 42 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	SPECIAL
TL/TT	TL
LI/SS	183 D

DIMENSIONS IS STANDARD

SW (MM)	606	RIM REC	DW20B
OD (MM)	2058	RIM ALT	DW18B ; MW20B
SLR (MM)	923	ECE	E11-106R-006444
RC (MM)	6166	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
70	3425	3980	4540	5095	5655	6210	6850	7245	7960
FROM 65 TO 40	3765	4375	4990	5600	6215	6825	7525	7965	8750
30	3840	4465	5090	5715	6340	6965	7680	8125	8925
20	3915	4550	5190	5825	6465	7100	7830	8285	9100
10	4140	4815	5490	6160	6835	7510	8280	8760	9625
UPTO 30 CYC	4270	4965	5665	6360	7055	7750	8540	9040	9930
UPTO 15 CYC	5100	5930	6760	7590	8420	9250	10200	10790	11855
UPTO 10 CYC	5590	6495	7405	8315	9225	10135	11175	11825	12990
10 HT	3840	4465	5090	5715	6340	6965	7680	8125	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.