

AGRIMAX FORCE

TYRE SIZE	IF 900/60 R 42 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	186 D



DIMENSIONS IS STANDARD

SW (MM)	916	RIM REC	DW 30 B
OD (MM)	2147	RIM ALT	TW 30 B
SLR (MM)	950	ECE	E11-106R-006494
RC (MM)	6416	SRI	1025

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3975	4580	5270	5875	6570	7175	8035	8645
FROM 65 TO 40	4370	5035	5795	6460	7220	7885	8835	9500
30	4540	5235	6025	6715	7505	8200	9185	9880
20	4715	5435	6255	6975	7795	8515	9540	10260
10	5545	6390	7355	8200	9165	10010	11220	12065
UPTO 30 CYC	5680	6545	7530	8395	9385	10250	11485	12350
UPTO 15 CYC	6770	7800	8980	10010	11190	12220	13690	14725
UPTO 10 CYC	7425	8555	9850	10980	12270	13400	15015	16150
10HT	4540	5235	6025	6715	7505	8200	9185	9880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.