DATA SHEET

Latest update
3-08-2026

V-FLEXA



TYRE SIZE	**VF 600/65 R 26.5**
UM	IS STANDARD
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	172 D

DIMENSIONS IS STANDARD

SW (MM)	615	**RIM REC**	AG20.00
OD (MM)	1453	**ECE**	E11-106R-006624
SLR (MM)	628	**SRI**	700
RC (MM)	4377	**TREAD DEPTH (MM)**	24,5

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8
70	2470	3155	3845	4360	5050	5735
65	2710	3465	4225	4790	5545	6300
50	3175	4060	4945	5605	6490	7375
40	3500	4475	5450	6180	7155	8130
10	4445	5685	6925	7855	9095	10335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.