

## LG 306

|                  |                                 |
|------------------|---------------------------------|
| <b>TIRE SIZE</b> | <b>44X18.00 -20</b>             |
| <b>UM</b>        | IS STANDARD                     |
| <b>MACHINERY</b> | MOWER / SMALL TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                        |
| <b>TL/TT</b>     | TL                              |



### DIMENSIONS IS STANDARD

|                 |        |                         |                 |
|-----------------|--------|-------------------------|-----------------|
| <b>SW (MM)</b>  | 490    | <b>RIM ALT</b>          | W 14 LH         |
| <b>OD (MM)</b>  | 1165   | <b>ECE</b>              | E11-106R-006828 |
| <b>SLR (MM)</b> | 518    | <b>PR</b>               | 4               |
| <b>RC (MM)</b>  | 3509   | <b>TREAD DEPTH (MM)</b> | 19,5            |
| <b>RIM REC</b>  | W 14 L |                         |                 |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.40</b> |
| 50                | 1550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.