

# RIDEMAX FL 690

|                  |                                         |
|------------------|-----------------------------------------|
| <b>TIRE SIZE</b> | <b>VF 900/65 R 32</b>                   |
| <b>UM</b>        | IS STANDARD                             |
| <b>MACHINERY</b> | TANKER / TRAILER / IMPLEMENTS / TRAILER |
| <b>VERSION</b>   | STANDARD                                |
| <b>TL/TT</b>     | TL                                      |
| <b>LI/SS</b>     | 197 D                                   |



## DIMENSIONS IS STANDARD

|                 |         |                         |                 |
|-----------------|---------|-------------------------|-----------------|
| <b>OD (MM)</b>  | 1986    | <b>RIM ALT</b>          | DW 30 ; TW 30   |
| <b>SLR (MM)</b> | 838     | <b>ECE</b>              | E11-106R-006917 |
| <b>RC (MM)</b>  | 5878    | <b>SRI</b>              | 925             |
| <b>RIM REC</b>  | DW 31 B | <b>TREAD DEPTH (MM)</b> | 31              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2   | 1.6   | 2.0   | 2.4   | 2.8   |
|------------|------|-------|-------|-------|-------|-------|
| 70         | 5030 | 6435  | 7840  | 8890  | 10295 | 11695 |
| 65         | 5530 | 7070  | 8610  | 9770  | 11310 | 12850 |
| 50         | 6470 | 8270  | 10075 | 11430 | 13235 | 15035 |
| 40         | 7130 | 9120  | 11110 | 12605 | 14595 | 16580 |
| 10         | 9065 | 11595 | 14125 | 16020 | 18550 | 21075 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.