

# AGRIMAXFACTOR

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 710/70 R 42                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR                                                                                  |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 176 D ; 179 A8                                                                           |



## DIMENSIONS IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 716  | RIM REC | DW 23 B         |
| OD (MM)  | 2061 | RIM ALT | DW 25 B         |
| SLR (MM) | 935  | ECE     | E11-106R-007525 |
| RC (MM)  | 6198 | SRI     | 975             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  |
|------------|------|------|------|------|------|------|------|------|------|
| 65         | 3055 | 3550 | 4050 | 4545 | 5045 | 5540 | 6110 | 6465 | 7100 |
| 50         | 3210 | 3730 | 4250 | 4775 | 5295 | 5815 | 6415 | 6785 | 7455 |
| 40         | 3335 | 3875 | 4420 | 4960 | 5505 | 6045 | 6665 | 7055 | 7750 |
| 30         | 3515 | 4085 | 4655 | 5230 | 5800 | 6370 | 7025 | 7435 | 8165 |
| 10 LT      | 4095 | 4760 | 5425 | 6090 | 6760 | 7425 | 8185 | 8660 | 9515 |
| 10 HT      | 3515 | 4085 | 4655 | 5230 | 5800 | 6370 | 7025 | 7435 | 8165 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.