DATA SHEET

Latest update
28-07-2026

AGRIMAX TURF RT 333



TYRE SIZE	**220/55 R 12**
UM	IS STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	82 A8/B

DIMENSIONS IS STANDARD

SW (MM)	221	**ECE**	E11-106R-007600
OD (MM)	550	**SRI**	260
SLR (MM)	249	**TREAD DEPTH (MM)**	14,5
RC (MM)	1645	**TKPH (TK/H)**	0
RIM REC	7		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	225	265	300	335	370	395	445	475
40	225	265	300	335	370	395	445	475
30	240	285	325	360	395	425	475	510
10 LT	305	355	405	450	495	535	600	640
10 HT	240	285	325	360	395	425	475	510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.