DATA SHEET

Latest update
4-08-2026

AGRIMAX TURF RT 333



TYRE SIZE	**240/60 R 12**
UM	IS STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	89 A8 ; B

DIMENSIONS IS STANDARD

SW (MM)	242	**RIM REC**	7
OD (MM)	592	**ECE**	E11-106R-007679
SLR (MM)	269	**TREAD DEPTH (MM)**	14,5
RC (MM)	1777		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	270	310	355	395	445	485	540	580
40	270	310	355	395	445	485	540	580
30	290	335	385	425	475	520	585	625
10 LT	360	415	480	535	595	650	730	780
10 HT	290	335	385	425	475	520	585	625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.