DATA SHEET

Latest update
3-08-2026

RIDEMAX IT 697 (M+S)



TIRE SIZE	**540/70 R 24 IND**
UM	IS STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	170 D ; 175 A8

DIMENSIONS IS STANDARD

SW (MM)	535	**RIM ALT**	DW18 L
OD (MM)	1370	**ECE**	E11-106R-007933
SLR (MM)	625	**SRI**	650
RC (MM)	4181	**TREAD DEPTH (MM)**	26,5
RIM REC	DW 16 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
65	2040	2520	2760	3240	3660	4080	4500	4920	5460	6000
50	2205	2725	2985	3500	3955	4410	4860	5315	5900	6480
40	2350	2900	3175	3730	4210	4695	5175	5660	6280	6900
30	2450	3025	3315	3890	4395	4900	5400	5905	6555	7200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.