

## V-FLEXA

|                  |                         |
|------------------|-------------------------|
| <b>TYRE SIZE</b> | <b>VF 710/50 R 26.5</b> |
| <b>UM</b>        | IS STANDARD             |
| <b>MACHINERY</b> | TRAILER / IMPLEMENTS    |
| <b>VERSION</b>   | STEEL BELTED            |
| <b>TL/TT</b>     | TL                      |
| <b>LI/SS</b>     | 176 D                   |



### DIMENSIONS IS STANDARD

|                 |      |                         |                 |
|-----------------|------|-------------------------|-----------------|
| <b>SW (MM)</b>  | 727  | <b>RIM REC</b>          | AG 24.00        |
| <b>OD (MM)</b>  | 1383 | <b>ECE</b>              | E11-106R-008833 |
| <b>SLR (MM)</b> | 600  | <b>SRI</b>              | 650             |
| <b>RC (MM)</b>  | 4193 | <b>TREAD DEPTH (MM)</b> | 24,5            |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8   | 3.2   |
|------------|------|------|------|------|------|-------|-------|
| 70         | 2590 | 3300 | 3880 | 4530 | 5110 | 5820  | 6465  |
| 65         | 2840 | 3625 | 4260 | 4970 | 5610 | 6390  | 7100  |
| 50         | 3325 | 4240 | 4990 | 5820 | 6565 | 7480  | 8310  |
| 40         | 3665 | 4675 | 5500 | 6415 | 7240 | 8245  | 9160  |
| 10         | 4660 | 5940 | 6990 | 8155 | 9200 | 10485 | 11645 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.