DATA SHEET

Latest update
3-08-2026

AGRIMAX TURF RT 333



TYRE SIZE	**480/70 R 30**
UM	IS STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	141 A8 ; 141 B

DIMENSIONS IS STANDARD

SW (MM)	479	**RIM ALT**	W 14 L ; W 16 L
OD (MM)	1478	**ECE**	E11-106R-009050
SLR (MM)	660	**SRI**	700
RC (MM)	4396	**TREAD DEPTH (MM)**	30,5
RIM REC	W 15 L		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1420	1650	1880	2115	2345	2575
40	1420	1650	1880	2115	2345	2575
30	1520	1770	2015	2265	2515	2760
10 LT	1905	2215	2525	2835	3145	3455
10 HT	1520	1770	2015	2265	2515	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.