

RIDEMAX FL 693 M



TIRE SIZE	650/65 R 30.5
UM	IS STANDARD
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	176 D

DIMENSIONS IS STANDARD

SW (MM)	645	RIM REC	AG 20.00
OD (MM)	1623	ECE	E11-106R-009076
SLR (MM)	734	SRI	775
RC (MM)	4939	TREAD DEPTH (MM)	24,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2070	2395	2720	3300	3815	4400	4980	5370	5950	6465
65	2275	2630	2985	3625	4190	4830	5470	5895	6535	7100
50	2755	3185	3610	4385	5075	5845	6620	7135	7910	8595
40	3095	3580	4060	4930	5700	6570	7440	8020	8890	9660
25	3595	4155	4715	5725	6620	7630	8640	9315	10325	11220
10	4090	4730	5370	6520	7545	8695	9845	10610	11760	12780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.