

## AT 109

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>AT 22X11 -8</b>                                                                     |
| <b>UM</b>           | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | ATV                                                                                    |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TL/TT</b>        | TL                                                                                     |



### DIMENSIONS IS STANDARD

|                 |     |                |                |
|-----------------|-----|----------------|----------------|
| <b>SW (MM)</b>  | 230 | <b>RIM REC</b> | 9.0 AT         |
| <b>OD (MM)</b>  | 579 | <b>RIM ALT</b> | 8.5 AT         |
| <b>SLR (MM)</b> | 0   | <b>ECE</b>     | E11-75R-004670 |
| <b>RC (MM)</b>  | 0   | <b>PR</b>      | 2              |

### LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>0.21</b> |
|-------------------|-------------|
| 100               | 112         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.