DATA SHEET

Latest update
4-07-2026



AW 09

TYRE SIZE	**260/70 - 15.3**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENT MACHINERY / TRAILER / HAY HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS DRIVE WHEEL	110 A8
LI/SS FREE ROLLING	122 A8

DIMENSIONS IS STANDARD

SW (MM)	268	**RIM REC**	9.00
OD (MM)	753	**ECE**	E4-106R-000372
SLR (MM)	335		
RC (MM)	2206		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	3.20
10 FR	2100
25 FR	1785
30 FR	1680
40 FR	1500
10 DW	1485
25 DW	1260
30 DW	1185
40 DW	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..