

# RIDEMAX FL 693 M



|                  |                               |
|------------------|-------------------------------|
| <b>TIRE SIZE</b> | <b>560/55 R 22.5</b>          |
| <b>UM</b>        | IS STANDARD                   |
| <b>MACHINERY</b> | TANKER / TRAILER / IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                      |
| <b>TL/TT</b>     | TL                            |
| <b>LI/SS</b>     | 158 D ; 155 E                 |

## DIMENSIONS IS STANDARD

|                 |          |                         |                |
|-----------------|----------|-------------------------|----------------|
| <b>SW (MM)</b>  | 543      | <b>RIM ALT</b>          | 17.00 ; 20.00  |
| <b>OD (MM)</b>  | 1180     | <b>ECE</b>              | E4-106R-000631 |
| <b>SLR (MM)</b> | 533      | <b>SRI</b>              | 550            |
| <b>RC (MM)</b>  | 3614     | <b>TREAD DEPTH (MM)</b> | 20,5           |
| <b>RIM REC</b>  | AG 16.00 |                         |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|
| 70         | 1435 | 1630 | 1940 | 2290 | 2620 | 2910 | 3255 | 3565 | 3875 |
| 65         | 1575 | 1785 | 2125 | 2510 | 2870 | 3190 | 3570 | 3910 | 4250 |
| 50         | 1910 | 2165 | 2575 | 3040 | 3475 | 3860 | 4325 | 4735 | 5145 |
| 40         | 2140 | 2430 | 2890 | 3415 | 3905 | 4335 | 4860 | 5320 | 5780 |
| 25         | 2490 | 2825 | 3360 | 3965 | 4535 | 5040 | 5645 | 6180 | 6715 |
| 10         | 2835 | 3215 | 3825 | 4515 | 5165 | 5740 | 6430 | 7040 | 7650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.