

## AGRIMAX RT 765

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 260/70 R 20                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR / IMPLEMENTS                                                                     |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 113 A8/B                                                                                 |



### DIMENSIONS IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 258  | RIM REC | W 8            |
| OD (MM)  | 872  | RIM ALT | 9 ; W 9        |
| SLR (MM) | 402  | ECE     | E4-106R-000640 |
| RC (MM)  | 2639 | SRI     | 425            |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|-----|-----|-----|------|------|------|------|------|
| 50         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 40         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 30         | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |
| 10 LT      | 730 | 835 | 960 | 1085 | 1210 | 1330 | 1440 | 1545 |
| 10 HT      | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.