

# AGRIMAX RT 955

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 270/95 R 38                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | SPRAYER / VINEYARD HARVESTER /<br>HARVESTER / IMPLEMENTS                                 |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 140 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 275  | RIM REC | W 9            |
| OD (MM)  | 1479 | RIM ALT | W 8 ; W 10     |
| SLR (MM) | 697  | ECE     | E4-106R-000657 |
| RC (MM)  | 4510 | SRI     | 700            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50         | 975  | 1275 | 1550 | 1700 | 1800 | 1975 | 2150 | 2325 | 2500 | -    |
| 40         | 975  | 1275 | 1550 | 1700 | 1800 | 1975 | 2150 | 2325 | 2500 | -    |
| 30         | 1045 | 1365 | 1660 | 1820 | 1930 | 2115 | 2305 | 2490 | 2675 | -    |
| 10         | 1165 | 1465 | 1800 | 2140 | 2475 | 2550 | 2850 | 3150 | 3450 | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.