

RIDEMAX FL 693 M



TIRE SIZE	580/65 R 22.5
UM	IS STANDARD
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	166 D ; 163 E

DIMENSIONS IS STANDARD

SW (MM)	577	RIM ALT	AG 16.00 ; AG 17.00 ; AG 20.00
OD (MM)	1326	ECE	E4-106R-000804
SLR (MM)	572	SRI	625
RC (MM)	4031	TREAD DEPTH (MM)	20,5
RIM REC	AG 18.00		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1805	2050	2440	2880	3295	3660	4095	4485	4875
65	1965	2230	2650	3130	3580	3975	4455	4880	5300
50	2375	2695	3210	3785	4335	4815	5390	5905	6415
40	2670	3030	3605	4255	4870	5410	6060	6635	7210
25	3100	3520	4190	4945	5655	6285	7035	7705	8375
10	3535	4010	4770	5630	6440	7155	8015	8780	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.