

AGRIMAX RT 600

TYRE SIZE	1050/50 R 32
UM	IS STANDARD
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	184 A8 ; 181 B



DIMENSIONS IS STANDARD

SW (MM)	1059	RIM REC	36.0 VA (multipiece)
OD (MM)	1863	ECE	E4-106R-000813
SLR (MM)	826	SRI	875
RC (MM)	5700	TREAD DEPTH (MM)	46,5

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	3715	4210	5280	5860	6520	7015	7675	8250	-	-
40	4050	4590	5760	6390	7110	7650	8370	9000	-	-
30	4335	4915	6165	6840	7610	8190	8960	9630	-	-
10 LT	5430	6155	7720	8565	9530	10255	11220	12060	-	-
10 HT	4335	4915	6165	6840	7610	8190	8960	9630	-	-
10 CYC	-	6810	8725	9565	11095	11555	12645	13595	14195	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.