

# AGRIMAX FORTIS



|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 600/70 R 34                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR                                                                                  |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 160 D ; 163 A8                                                                           |

## DIMENSIONS IS STANDARD

|          |      |         |                  |
|----------|------|---------|------------------|
| SW (MM)  | 591  | RIM REC | DW 18 L          |
| OD (MM)  | 1704 | RIM ALT | DW 20 B ; W 18 L |
| SLR (MM) | 761  | ECE     | E4-106R-001401   |
| RC (MM)  | 5109 | SRI     | 800              |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2160 | 2520 | 2835 | 3150 | 3465 | 3735 | 4140 | 4500 |
| 50         | 2270 | 2650 | 2980 | 3310 | 3640 | 3925 | 4350 | 4725 |
| 40         | 2340 | 2730 | 3075 | 3415 | 3755 | 4050 | 4485 | 4875 |
| 30         | 2485 | 2900 | 3265 | 3625 | 3985 | 4300 | 4765 | 5175 |
| 10 LT      | 2895 | 3380 | 3800 | 4225 | 4645 | 5005 | 5550 | 6030 |
| 10 HT      | 2485 | 2900 | 3265 | 3625 | 3985 | 4300 | 4765 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.