

## FL 630 ULTRA

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 500/60 R 22.5                                                                            |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRAILER / IMPLEMENTS                                                                     |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 155 D ; 166 A8                                                                           |



### DIMENSIONS IS STANDARD

|          |      |         |                       |
|----------|------|---------|-----------------------|
| SW (MM)  | 503  | RIM REC | AG 16.00              |
| OD (MM)  | 1172 | RIM ALT | 15.00 ; 16.00 ; 17.00 |
| SLR (MM) | 521  | ECE     | E4-106R-001404        |
| RC (MM)  | 3592 | SRI     | 550                   |

### LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1130 | 1310 | 1485 | 1780 | 2085 | 2385 | 2670 | 2970 | 3250 | 3530 |
| 65         | 1240 | 1435 | 1630 | 1950 | 2290 | 2610 | 2930 | 3255 | 3565 | 3875 |
| 50         | 1505 | 1740 | 1970 | 2345 | 2770 | 3160 | 3540 | 3940 | 4315 | 4690 |
| 40         | 1700 | 1965 | 2230 | 2680 | 3110 | 3560 | 3990 | 4440 | 4880 | 5300 |
| 25         | 1960 | 2270 | 2575 | 3080 | 3615 | 4110 | 4630 | 5130 | 5635 | 6125 |
| 10         | 2235 | 2585 | 2930 | 3500 | 4100 | 4700 | 5250 | 5850 | 6420 | 6975 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.