

# AGRIMAX RT 855

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 520/85 R 46                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR / IMPLEMENTS                                                                     |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 158 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|          |      |         |                                   |
|----------|------|---------|-----------------------------------|
| SW (MM)  | 516  | RIM REC | DW 16 L ; W 16 A ; W 16 L ; DD 16 |
| OD (MM)  | 2052 | RIM ALT | DW 18 L ; W 18 L ; W 18 A         |
| SLR (MM) | 930  | ECE     | E4-106R-001415                    |
| RC (MM)  | 6157 | SRI     | 975                               |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 2340 | 2720 | 3105 | 3485 | 3870 | 4250 |
| 40         | 2340 | 2720 | 3105 | 3485 | 3870 | 4250 |
| 30         | 2505 | 2915 | 3325 | 3735 | 4145 | 4550 |
| 10 LT      | 3135 | 3645 | 4160 | 4670 | 5185 | 5695 |
| 10 HT      | 2505 | 2915 | 3325 | 3735 | 4145 | 4550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.