

# AGRIMAX TERIS

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 620/75 R 30 CHO                                                                          |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HARVESTER / COTTON PICKER                                                                |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 168 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 625  | RIM REC | DW 20 B        |
| OD (MM)  | 1692 | ECE     | E4-106R-001420 |
| SLR (MM) | 779  | SRI     | 800            |
| RC (MM)  | 5169 |         |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2   |
|------------|------|------|------|------|------|------|------|-------|
| 50         | 2580 | 2970 | 3640 | 3980 | 4370 | 4760 | 5155 | 5600  |
| 40         | 2580 | 2970 | 3640 | 3980 | 4370 | 4760 | 5155 | 5600  |
| 30         | 2760 | 3180 | 3900 | 4260 | 4680 | 5100 | 5520 | 5995  |
| 15 CYC     | 4255 | 4900 | 6010 | 6565 | 7210 | 7855 | 8505 | 9240  |
| 10 CYC     | 4640 | 5345 | 6555 | 7160 | 7865 | 8570 | 9275 | 10080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.