

# AGRIMAX TERIS

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 800/65 R 32 CHO                                                                          |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HARVESTER / COTTON PICKER                                                                |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 178 A8 ; 175 B                                                                           |



## DIMENSIONS IS STANDARD

|          |      |         |                   |
|----------|------|---------|-------------------|
| SW (MM)  | 818  | RIM REC | DW 27 B           |
| OD (MM)  | 1853 | RIM ALT | DW 25 B ; DH 27 B |
| SLR (MM) | 838  | ECE     | E4-106R-001430    |
| RC (MM)  | 5551 | SRI     | 875               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.4  | 1.6  | 2.0   | 2.4   | 2.8   | 3.2   |
|------------|------|------|------|------|-------|-------|-------|-------|
| 50         | 3175 | 3660 | 4485 | 4900 | 5455  | 5865  | 6420  | 6900  |
| 40         | 3450 | 3975 | 4875 | 5325 | 5925  | 6375  | 6975  | 7500  |
| 30         | 3695 | 4255 | 5220 | 5700 | 6340  | 6825  | 7465  | 8025  |
| 15 CYC     | 5695 | 6560 | 8045 | 8790 | 9780  | 10520 | 11510 | 12375 |
| 10 CYC     | 6210 | 7155 | 8775 | 9585 | 10665 | 11475 | 12555 | 13500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.