

# AGRIMAX RT 855

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 520/85 R 42                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR / IMPLEMENTS                                                                     |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 167 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|          |      |         |                                    |
|----------|------|---------|------------------------------------|
| SW (MM)  | 540  | RIM REC | DW 16 L ; W 16 A ; DD 16           |
| OD (MM)  | 1951 | RIM ALT | DW 18 A ; DD 18 ; W 18 A ; DD 18 L |
| SLR (MM) | 895  | ECE     | E4-106R-001491                     |
| RC (MM)  | 5919 | SRI     | 925                                |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 2270 | 2640 | 3015 | 3385 | 3755 | 4125 | 4635 | 5070 | 5450 |
| 40         | 2270 | 2640 | 3015 | 3385 | 3755 | 4125 | 4635 | 5070 | 5450 |
| 30         | 2430 | 2830 | 3225 | 3625 | 4020 | 4415 | 4960 | 5425 | 5830 |
| 10 LT      | 3045 | 3540 | 4040 | 4535 | 5035 | 5530 | 6210 | 6795 | 7305 |
| 10 HT      | 2430 | 2830 | 3225 | 3625 | 4020 | 4415 | 4960 | 5425 | 5830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.