

# FLOTATION 648

|                           |                            |
|---------------------------|----------------------------|
| <b>TYRE SIZE</b>          | <b>700/50 - 22.5</b>       |
| <b>UM</b>                 | IS STANDARD                |
| <b>MACHINERY</b>          | HAY HARVESTER / IMPLEMENTS |
| <b>VERSION</b>            | STANDARD                   |
| <b>TL/TT</b>              | TL                         |
| <b>LI/SS DRIVE WHEEL</b>  | 162 A8/158 B               |
| <b>LI/SS FREE ROLLING</b> | 174 A8/170 B               |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 700  | <b>RIM REC</b> | 24.00          |
| <b>OD (MM)</b>  | 1270 | <b>ECE</b>     | E4-106R-001566 |
| <b>SLR (MM)</b> | 550  | <b>PR</b>      | 16             |
| <b>RC (MM)</b>  | 3775 |                |                |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR   | 2.00 | 2.20 | 2.40 |
|--------------|------|------|------|
| <b>10 FR</b> | 8430 | 8910 | 9380 |
| <b>20 FR</b> | 7585 | 8020 | 8440 |
| <b>30 FR</b> | 6740 | 7130 | 7505 |
| <b>40 FR</b> | 6020 | 6365 | 6700 |
| <b>50 FR</b> | 5420 | 5730 | 6000 |
| <b>10 DW</b> | 5980 | 6320 | 6650 |
| <b>20 DW</b> | 5380 | 5690 | 5985 |
| <b>30 DW</b> | 4780 | 5055 | 5320 |
| <b>40 DW</b> | 4270 | 4515 | 4750 |
| <b>50 DW</b> | 3845 | 4065 | 4250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.