

FL 630 SUPER

TYRE SIZE	750/45 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	170 D



DIMENSIONS IS STANDARD

SW (MM)	754	RIM REC	AG 24.00
OD (MM)	1349	ECE	E4-106R-001652
SLR (MM)	606	SRI	650
RC (MM)	4147		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1750	1995	2240	2785	3170	3660	4150	4535	4970	5460
65	1920	2190	2460	3060	3480	4020	4560	4980	5460	6000
50	2325	2655	2980	3705	4215	4865	5520	6030	6610	7260
40	2615	2985	3350	4165	4735	5470	6205	6775	7430	8160
25	3035	3465	3890	4835	5500	6355	7205	7870	8630	9480
10	3460	3945	4430	5510	6265	7240	8210	8965	9830	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.