

## TF 8181

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>4.50 - 16</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | 2WD TRACTOR / TRACTOR / TRAILER                                                        |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TL/TT</b>        | TT                                                                                     |
| <b>LI/SS</b>        | 73 A6                                                                                  |



### DIMENSIONS IS STANDARD

|                 |      |                 |                |
|-----------------|------|-----------------|----------------|
| <b>SW (MM)</b>  | 122  | <b>RIM REC</b>  | 3.00 D         |
| <b>OD (MM)</b>  | 655  | <b>ECE</b>      | E4-106R-001953 |
| <b>SLR (MM)</b> | 311  | <b>PR</b>       | 4              |
| <b>RC (MM)</b>  | 1952 | <b>TRA CODE</b> | F2             |

### LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.10</b> |
| 30                | 365         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.